

Spiral-Lock (Teflon) 600

Specifications
October 2022

Construction: Double-ply construction Teflon® fabric hose with a heat-resistant fiberglass liner mechanically crimped in a continuous process

Product Features:

- * Fabric is locked around a coated steel wire by a metal strip formed into a clip
- * Metal strip acts as a wearstrip
- * Outstanding resistance to external abrasion
- * Extremely flexible
- * Ideal for venting many of today's harsh chemicals
- * Available with a polyurethane (PU-75 shore material) clip cover to protect the helix & the equipment that is attached to the hose

Application: Fume.

Temperature Range: - 60 F to + 600 F

Sizes I.D. (inches): 4, 6, 8, 10, and 12 Inch I.D.

ID Tolerances: -0.00 to + 0.125 Inch

Standard Length: 25 Feet

Standard Colors: Black

End Finish: Plain Cut

Markets: Chemical Plants, Fume Exhaust, High Temperature Applications, Pharmaceuticals, and Pollution Control

Rubber-Cal, Inc.
18424 Mt Langley St,
Fountain Valley, CA 92708
800-370-9152
www.ducting.com



Spiral-Lock (Teflon) 600

Specifications
October 2022

Size Inside Diameter (Inches)	Approximate Weight Lbs./ft.	Min Centerline Bend Radius (Inches)	Compression Ratio	Max Recommended Negative Pressure (IN./HG)	Max Recommended Positive Pressure (PSI)
3	0.69	3.5	3 to 1	8	11.2
4	0.87	4	3 to 1	7	9
5	0.81	4.5	5 to 1	6	7
6	0.96	5	5 to 1	4	6
7	1.18	5.5	5 to 1	3.8	5.2
8	1.33	6.5	5 to 1	3.5	4.5
9	1.47	7.3	5 to 1	3.3	3.7
10	1.61	8	5 to 1	3	3.2
12	1.85	9.5	5 to 1	2.5	2.8
14	2.25	11	5 to 1	1.75	2.2
16	2.58	12	5 to 1	1.5	1.9

Note: Technical data based on 2 ft. straight lengths of hose 72 F.

Disclaimer: The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

California Prop 65: ⚠️ **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Rubber-Cal, Inc.
18424 Mt Langley St,
Fountain Valley, CA 92708
800-370-9152
www.ducting.com

